

### AMENDMENTS TO THE CLAIMS

The following listing of claims replaces all prior versions and listings.

1. (Currently Amended) A safety cycle pedal including a pedal body mounted to rotate about a pedal spindle, said safety cycle pedal comprising:
  - a first rear hoop comprising ~~an~~ a first rear attachment bar situated behind the pedal spindle and substantially parallel to ~~this~~ the pedal spindle, the first rear hoop being articulated about a first hoop spindle mounted in bearings of the pedal body,
  - a first front hoop comprising ~~an~~ a first front attachment bar situated in front of the pedal spindle and substantially parallel to ~~this~~ the pedal spindle, the first front hoop being articulated about a second hoop spindle,
  - elastic means urging the first rear hoop and the first front hoop toward a rest position in which a mid-plane of the first front hoop and a mid-plane of the first rear hoop are substantially orthogonal to a mid-plane of the pedal, wherein:
    - the front and rear attachment bars ~~being~~ are situated above the pedal body and ~~being~~ are able to be moved apart in order to allow the passage and attachment of a cleat fixed under ~~the~~ a sole of a cycle shoe in a housing of the sole, at least one edge of which is limited by a ~~projection, especially a stud~~ [[,]] whose thickness is ~~generally~~ greater than ~~that a~~ a thickness of the cleat [[,]];
    - ~~wherein~~ the second hoop spindle ~~for the articulation of the front hoop~~ is situated below ~~the~~ a mid-plane of the pedal passing through ~~the~~ a geometric axis of the pedal, on ~~the~~ an opposite side to the front attachment bar [[,]]; and
    - the a front upper part of the pedal body is limited by a front face inclined downward toward ~~the~~ its front, allowing a greater angular range for clicking in.

2. (Currently Amended) The cycle pedal as claimed in claim 1, wherein the inclination of the front face relative to the mid-plane of the pedal is about 40°, said front face constituting a zone on which blocks of the sole may slide during interlocking.
3. (Currently Amended) The cycle pedal as claimed in claim 1, wherein the angular range for clicking in ~~may reach~~ is 25°.
4. (Currently Amended) The cycle pedal as claimed in claim 1, wherein ~~sufficient~~ material is retained around the bearings through which the second hoop spindle passes.
5. (Currently Amended) The cycle pedal of claim 1, ~~wherein said cycle pedal is equipped with hoops and attachment means on each of two faces, further comprising:~~  
a second rear hoop integral with the first front hoop so as to form a rectangular frame, said second rear hoop comprising a second rear attachment bar;  
and  
a second front hoop integral with the first rear hoop so as to form a rectangular frame, said second front hoop comprising a second front attachment bar, wherein said first front hoop and said first rear hoop are located at a top face of the pedal, and wherein the second front hoop and the second rear hoop are located at a bottom face of the pedal and wherein the front hoop of one face is integral with the rear hoop of the other face, the two hoops forming a substantially rectangular frame.
6. (Currently Amended) The cycle pedal as claimed in claim 1, comprising, to the rear of the body, a ~~kind of~~ cap provided for guiding the sole of a shoe fitted with a tunnel, wherein the rear hoop bears against the cap in the rest position.

7. (Currently Amended) The cycle pedal as claimed in claim 1, wherein each said first front hoop comprises at least one lateral stop provided in order to limiting the freedom of transverse displacement of a cleat fixed under a shoe.

8. (Currently Amended) The cycle pedal as claimed in claim 1, wherein each said first front hoop comprises at least one lug projecting to the an inside of the first front hoop from a leg which is substantially orthogonal to the first front attachment bar, said at least one lug projecting substantially halfway between a hole for a passage of the second hoop spindle and the first front attachment bar.

9. (Currently Amended) The cycle pedal as claimed in claim ~~[[8]]~~ 1, wherein ~~each of the legs of a hoop comprises a lug~~ said first front hoop comprises legs substantially orthogonal to said first front attachment bar, and wherein each of said legs comprises a lug projecting to an inside of the first front hoop, said lug projecting substantially halfway between a hole for a passage of the second hoop spindle and the first front attachment bar.

10. (Canceled)

11. (Currently Amended) The cycle pedal as claimed in claim ~~[[10]]~~ 12, wherein the bearing piece is formed by an adjusting rod mounted to rotate in the pedal body and comprising planar faces situated at different distances from the geometric axis of rotation of the rod.

12. (New) A safety cycle pedal including a pedal body mounted to rotate about a pedal spindle, said safety cycle pedal comprising:

- a first rear hoop comprising a first rear attachment bar situated behind the pedal spindle and substantially parallel to the pedal spindle, the first rear hoop being articulated about a first hoop spindle mounted in bearings of the pedal body,

- a first front hoop comprising a first front attachment bar situated in front of the pedal spindle and substantially parallel to the pedal spindle, the first front hoop being articulated about a second hoop spindle, the first front hoop comprising at least one lug projecting to an inside of the first front hoop from a leg which is substantially orthogonal to the first front attachment bar,
- elastic means comprising two separate torsion springs with windings whose axes are aligned, one end of said windings bearing against said at least one lug and another end of said windings bearing against a bearing piece made of a material harder than that of the pedal body, said elastic means urging the first rear hoop and the first front hoop toward a rest position in which a mid-plane of the first front hoop and a mid-plane of the first rear hoop are substantially orthogonal to a mid-plane of the pedal, wherein:

the front and rear attachment bars are situated above the pedal body and are able to be moved apart in order to allow the passage and attachment of a cleat fixed under a sole of a cycle shoe in a housing of the sole, at least one edge of which is limited by a stud whose thickness is greater than a thickness of the cleat;

the second hoop spindle is situated below a mid-plane of the pedal passing through a geometric axis of the pedal, on an opposite side to the front attachment bar; and

a front upper part of the pedal body is limited by a front face inclined downward toward its front, allowing a greater angular range for clicking in.